

## Film Performance

<b>3M Color Stable Series</b>	<b>CS5</b>	<b>CS20</b>	<b>CS35</b>		<b>3M Night Vision Series</b>	<b>NV15</b>	<b>NV25</b>	<b>NV35</b>		
Visible Light Transmitted	9%	19%	39%		Visible Light Transmitted	13%	24%	33%		
UV Rejected	99%	99%	99%		UV Rejected	99.9%	99.9%	99.9%		
Total Solar Energy Rejected	57%	51%	40%		Total Solar Energy Rejected	72%	63%	54%		
<b>3M Ceramic IR Series</b>	<b>CMIR15</b>	<b>CMIR35</b>	<b>CMIR50</b>	<b>CMIR70</b>	<b>3M Prestige Series</b>	<b>PR20</b>	<b>PR40</b>	<b>PR50</b>	<b>PR60</b>	<b>PR70</b>
Visible Light Transmitted	19%	45%	60%	78%	Visible Light Transmitted	21%	39%	50%	60%	69%
UV Rejected	99%	99%	99%	99%	UV Rejected	99.9%	99.9%	99.9%	99.9%	99.9%
Infrared Rejected*	90%	85%	83%	78%	Total Solar Energy Rejected	62%	60%	56%	53%	50%
Total Solar Energy Rejected	59%	52%	47%	41%	TSER – On 60 Degree Angle	65%	66%	63%	61%	59%
					Infrared Rejected*	97%	97%	97%	97%	97%

Note:

- Performance data generated for a typical film on 1/4” clear glass using applicable industry test methods and standards.
- Infrared rejection as measured from 900-1000nm.